

APPENDIX

Exploration Logs

Coarse-Grained Soils - More than 50% (1) Retained on No. 200 Sieve			Terms Describing Relative Density and Consistency	
Gravels - More than 50% (1) of Coarse Fraction Retained on No. 4 Sieve	≤5% Fines (5)	GW	Well-graded gravel and gravel with sand, little to no fines	<u>Density</u> Very Loose 0 to 4 Loose 4 to 10 Medium Dense 10 to 30 Dense 30 to 50 Very Dense >50
Sands - 50% (1) or More of Coarse Fraction Passes No. 4 Sieve	≤5% Fines (5)	GP	Poorly-graded gravel and gravel with sand, little to no fines	<u>Consistency</u> Very Soft 0 to 2 Soft 2 to 4 Medium Stiff 4 to 8 Stiff 8 to 15 Very Stiff 15 to 30 Hard >30
Sands - 50% (1) or More of Coarse Fraction Passes No. 4 Sieve	≥15% Fines (5)	GM	Silty gravel and silty gravel with sand	Test Symbols G = Grain Size M = Moisture Content A = Atterberg Limits C = Chemical DD = Dry Density K = Permeability
Sands - 50% (1) or More of Coarse Fraction Passes No. 4 Sieve	≥15% Fines (5)	GC	Clayey gravel and clayey gravel with sand	Component Definitions <u>Descriptive Term</u> Boulders Larger than 12" Cobbles 3" to 12" Gravel 3" to No. 4 (4.75 mm) Coarse Gravel 3" to 3/4" Fine Gravel 3/4" to No. 4 (4.75 mm) Sand No. 4 (4.75 mm) to No. 200 (0.075 mm) Coarse Sand No. 4 (4.75 mm) to No. 10 (2.00 mm) Medium Sand No. 10 (2.00 mm) to No. 40 (0.425 mm) Fine Sand No. 40 (0.425 mm) to No. 200 (0.075 mm) Silt and Clay Smaller than No. 200 (0.075 mm)
Sands - 50% (1) or More of Coarse Fraction Passes No. 4 Sieve	≤5% Fines (5)	SW	Well-graded sand and sand with gravel, little to no fines	(3) Estimated Percentage <u>Component</u> Trace <5 Few 5 to 10 Little 15 to 25 With - Non-primary coarse constituents: ≥ 15% - Fines content between 5% and 15%
Sands - 50% (1) or More of Coarse Fraction Passes No. 4 Sieve	≥15% Fines (5)	SP	Poorly-graded sand and sand with gravel, little to no fines	Moisture Content Dry - Absence of moisture, dusty, dry to the touch Slightly Moist - Perceptible moisture Moist - Damp but no visible water Very Moist - Water visible but not free draining Wet - Visible free water, usually from below water table
Sands - 50% (1) or More of Coarse Fraction Passes No. 4 Sieve	≥15% Fines (5)	SM	Silty sand and silty sand with gravel	Symbols Sampler Type 2.0" OD Split-Spoon Sampler (SPT) Bulk sample Grab Sample Blows/6" or portion of 6" Sampler Type Description 3.0" OD Split-Spoon Sampler 3.25" OD Split-Spoon Ring Sampler 3.0" OD Thin-Wall Tube Sampler (including Shelby tube) Portion not recovered
Fine-Grained Soils - 50% (1) or More Passes No. 200 Sieve	Silt and Clays Liquid Limit Less than 50	ML	Silt, sandy silt, gravelly silt, silt with sand or gravel	(4) Depth of ground water ATD = At time of drilling Static water level (date) (5) Combined USCS symbols used for fines between 5% and 15%
Fine-Grained Soils - 50% (1) or More Passes No. 200 Sieve	Silt and Clays Liquid Limit 50 or More	CL	Clay of low to medium plasticity; silty, sandy, or gravelly clay, lean clay	(4) Depth of ground water ATD = At time of drilling Static water level (date) (5) Combined USCS symbols used for fines between 5% and 15%
Fine-Grained Soils - 50% (1) or More Passes No. 200 Sieve	Silt and Clays Liquid Limit Less than 50	OL	Organic clay or silt of low plasticity	(4) Depth of ground water ATD = At time of drilling Static water level (date) (5) Combined USCS symbols used for fines between 5% and 15%
Fine-Grained Soils - 50% (1) or More Passes No. 200 Sieve	Silt and Clays Liquid Limit 50 or More	MH	Elastic silt, clayey silt, silt with micaceous or diatomaceous fine sand or silt	(4) Depth of ground water ATD = At time of drilling Static water level (date) (5) Combined USCS symbols used for fines between 5% and 15%
Fine-Grained Soils - 50% (1) or More Passes No. 200 Sieve	Silt and Clays Liquid Limit 50 or More	CH	Clay of high plasticity, sandy or gravelly clay, fat clay with sand or gravel	(4) Depth of ground water ATD = At time of drilling Static water level (date) (5) Combined USCS symbols used for fines between 5% and 15%
Fine-Grained Soils - 50% (1) or More Passes No. 200 Sieve	Silt and Clays Liquid Limit 50 or More	OH	Organic clay or silt of medium to high plasticity	(4) Depth of ground water ATD = At time of drilling Static water level (date) (5) Combined USCS symbols used for fines between 5% and 15%
Highly Organic Soils		PT	Peat, muck and other highly organic soils	

Classifications of soils in this report are based on visual field and/or laboratory observations, which include density/consistency, moisture condition, grain size, and plasticity estimates and should not be construed to imply field or laboratory testing unless presented herein. Visual-manual and/or laboratory classification methods of ASTM D-2487 and D-2488 were used as an identification guide for the Unified Soil Classification System.

Associated Earth Sciences, Inc.



EXPLORATION LOG KEY

FIGURE A1

LOG OF EXPLORATION PIT NO. EP-1


Depth (ft)	<p>This log is part of the report prepared by Associated Earth Sciences, Inc. (AESI) for the named project and should be read together with that report for complete interpretation. This summary applies only to the location of this trench at the time of excavation. Subsurface conditions may change at this location with the passage of time. The data presented are a simplification of actual conditions encountered.</p> <p>DESCRIPTION</p>	
	Sod / Topsoil	
1	Weathered Vashon Lodgement Till	
2	Loose, moist, reddish brown, silty SAND, with gravel, scattered roots, scattered cobbles.	
	Becomes medium dense and tan, with no roots below 1.5 feet.	
3		
4	Vashon Lodgement Till	
5	Very dense, moist, grayish tan, silty SAND, with gravel (SM).	
6		
7	Bottom of exploration pit at depth 6 feet	
8	No seepage. No caving.	
9		
10		
11		
12		
13		
14		
15		
16		
17		
18		
19		
20		

**Eaglemont
Monroe, WA**

Associated Earth Sciences, Inc.

Project No. KE120280A

Logged by: TJP

Approved by: 



7/10/12

LOG OF EXPLORATION PIT NO. EP-2

Depth (ft)	<p>This log is part of the report prepared by Associated Earth Sciences, Inc. (AESI) for the named project and should be read together with that report for complete interpretation. This summary applies only to the location of this trench at the time of excavation. Subsurface conditions may change at this location with the passage of time. The data presented are a simplification of actual conditions encountered.</p> <p>DESCRIPTION</p>	
	Sod / Topsoil	
1	Weathered Vashon Lodgement Till	
2	Loose, moist, reddish brown, silty SAND, with gravel (SM); scattered cobbles; abundant roots from 0 to 2 feet.	
3	Becomes medium dense and tan below 2.5 feet.	
4	Vashon Lodgement Till	
5	Very dense, moist, grayish tan, silty SAND, with gravel (SM).	
6		
7	Bottom of exploration pit at depth 6 feet No seepage. No caving.	
8		
9		
10		
11		
12		
13		
14		
15		
16		
17		
18		
19		
20		

**Eaglemont
Monroe, WA**

Associated Earth Sciences, Inc.

Project No. KE120280A

Logged by: TJP

Approved by: *TOP*



7/10/12

LOG OF EXPLORATION PIT NO. EP-3


Depth (ft)	<p>This log is part of the report prepared by Associated Earth Sciences, Inc. (AESI) for the named project and should be read together with that report for complete interpretation. This summary applies only to the location of this trench at the time of excavation. Subsurface conditions may change at this location with the passage of time. The data presented are a simplification of actual conditions encountered.</p> <p>DESCRIPTION</p>	
	Sod / Topsoil	
1	Weathered Vashon Lodgement Till	
2	Loose, moist, reddish brown, silty SAND, with gravel (SM).	
3	Becomes medium dense and tan below 2.5 feet.	
4	Vashon Lodgement Till	
5	Very dense, moist, grayish tan, silty SAND, with gravel, scattered cobbles.	
6		
7	Bottom of exploration pit at depth 5.5 feet	
8	No seepage. No caving.	
9		
10		
11		
12		
13		
14		
15		
16		
17		
18		
19		
20		

**Eaglemont
Monroe, WA**

Associated Earth Sciences, Inc.

Project No. KE120280A

Logged by: TJP

Approved by: 



7/10/12

LOG OF EXPLORATION PIT NO. EP-4

Depth (ft)	<p>This log is part of the report prepared by Associated Earth Sciences, Inc. (AESI) for the named project and should be read together with that report for complete interpretation. This summary applies only to the location of this trench at the time of excavation. Subsurface conditions may change at this location with the passage of time. The data presented are a simplification of actual conditions encountered.</p> <p>DESCRIPTION</p>	
	Sod / Topsoil	
1	Weathered Vashon Lodgement Till	
2	Loose, moist, reddish brown, silty SAND, with gravel (SM).	
3	Becomes medium dense and tan below approximately 2 feet, scattered cobbles.	
4	Vashon Lodgement Till	
5	Very dense, moist, grayish tan, silty SAND, with gravel (SM); scattered cobbles.	
6	Bottom of exploration pit at depth 5 feet	
7	No seepage. No caving.	
8		
9		
10		
11		
12		
13		
14		
15		
16		
17		
18		
19		
20		

**Eaglemont
Monroe, WA**

Associated Earth Sciences, Inc.

Project No. KE120280A

Logged by: TJP

Approved by: *TJP*



7/10/12

LOG OF EXPLORATION PIT NO. EP-5

Depth (ft)	<p>This log is part of the report prepared by Associated Earth Sciences, Inc. (AESI) for the named project and should be read together with that report for complete interpretation. This summary applies only to the location of this trench at the time of excavation. Subsurface conditions may change at this location with the passage of time. The data presented are a simplification of actual conditions encountered.</p> <p>DESCRIPTION</p>	
	Forest Duff / Topsoil	
1	Weathered Vashon Lodgement Till	
	Loose, very moist, brown, silty SAND, with gravel, abundant roots (SM).	
2		
	Wet at base.	
3		
	Vashon Lodgement Till	
4	Very dense, very moist, grayish tan, silty SAND, with gravel (SM).	
	Becomes moist, contains scattered cobbles and boulders.	
5		
6	Bottom of exploration pit at depth 5.5 feet	
	Slow seepage at 3 feet. No caving.	
7		
8		
9		
10		
11		
12		
13		
14		
15		
16		
17		
18		
19		
20		

**Eaglemont
Monroe, WA**

Associated Earth Sciences, Inc.

Project No. KE120280A

Logged by: TJP

Approved by:

TJP



7/10/12

LOG OF EXPLORATION PIT NO. EP-6


Depth (ft)	<p>This log is part of the report prepared by Associated Earth Sciences, Inc. (AESI) for the named project and should be read together with that report for complete interpretation. This summary applies only to the location of this trench at the time of excavation. Subsurface conditions may change at this location with the passage of time. The data presented are a simplification of actual conditions encountered.</p> <p>DESCRIPTION</p>	
	Forest Duff / Topsoil	
1	Weathered Vashon Lodgement Till	
	Loose, very moist, reddish brown, silty SAND, with gravel, abundant roots (SM).	
2	Wet at base.	
	Vashon Lodgement Till	
3	Very dense, very moist, grayish tan, silty SAND, with gravel, scattered cobbles (SM).	
4		
5		
6	Bottom of exploration pit at depth 5.5 feet	
7	No seepage but sediments at base of weathered soil horizon (2.5 feet depth) appear close to saturated. No caving.	
8		
9		
10		
11		
12		
13		
14		
15		
16		
17		
18		
19		
20		

**Eaglemont
Monroe, WA**

Associated Earth Sciences, Inc.

Project No. KE120280A

Logged by: TJP

Approved by: 



7/10/12

LOG OF EXPLORATION PIT NO. EP-7

Depth (ft)	<p>This log is part of the report prepared by Associated Earth Sciences, Inc. (AESI) for the named project and should be read together with that report for complete interpretation. This summary applies only to the location of this trench at the time of excavation. Subsurface conditions may change at this location with the passage of time. The data presented are a simplification of actual conditions encountered.</p> <p>DESCRIPTION</p>	
	Forest Duff / Topsoil	
1	Weathered Vashon Lodgement Till	
	Loose, very moist, reddish brown, silty SAND, with gravel (SM).	
2	Becomes very moist below 1.5 feet.	
	Abundant roots from 0 to 2.5 feet.	
3	Vashon Lodgement Till	
	Dense to very dense, very moist, grayish tan, silty SAND, with gravel, scattered cobbles (SM).	
4		
5		
6	Bottom of exploration pit at depth 5.5 feet	
7	No seepage. No caving.	
8		
9		
10		
11		
12		
13		
14		
15		
16		
17		
18		
19		
20		

**Eaglemont
Monroe, WA**

Associated Earth Sciences, Inc.

Project No. KE120280A

Logged by: TJP

Approved by:




7/10/12

LOG OF EXPLORATION PIT NO. EP-8


Depth (ft)	<p>This log is part of the report prepared by Associated Earth Sciences, Inc. (AESI) for the named project and should be read together with that report for complete interpretation. This summary applies only to the location of this trench at the time of excavation. Subsurface conditions may change at this location with the passage of time. The data presented are a simplification of actual conditions encountered.</p> <p>DESCRIPTION</p>	
	Forest Duff / Topsoil	
1	Weathered Vashon Lodgement Till	
	Loose, very moist, reddish brown, silty SAND, with gravel, scattered cobbles (SM).	
2	Abundant roots from 0 to 2 feet.	
	Becomes medium dense and tan below 2 feet.	
3	Vashon Lodgement Till	
	Very dense, very moist, grayish tan, silty SAND, with gravel, scattered cobbles (SM).	
4	Becomes wet at approximately 4 feet.	
5		
6		
7	Bottom of exploration pit at depth 6.5 feet	
8	Slow seepage at 4 feet. No caving.	
9		
10		
11		
12		
13		
14		
15		
16		
17		
18		
19		
20		

**Eaglemont
Monroe, WA**

Associated Earth Sciences, Inc.

Project No. KE120280A

Logged by: TJP

Approved by: 



7/10/12

LOG OF EXPLORATION PIT NO. EP-9


Depth (ft)	<p>This log is part of the report prepared by Associated Earth Sciences, Inc. (AESI) for the named project and should be read together with that report for complete interpretation. This summary applies only to the location of this trench at the time of excavation. Subsurface conditions may change at this location with the passage of time. The data presented are a simplification of actual conditions encountered.</p> <p>DESCRIPTION</p>	
	Forest Duff / Topsoil	
1	Weathered Vashon Lodgement Till	
	Loose, very moist, reddish brown, silty SAND, with gravel, scattered cobbles (SM).	
2	Abundant roots from 0 to 2 feet.	
	Becomes medium dense and tan below 2 feet.	
3	Vashon Lodgement Till	
	Very dense, very moist, grayish tan, silty SAND, with gravel, scattered cobbles, and boulders (SM).	
4		
5		
6		
7	Bottom of exploration pit at depth 6 feet	
	No seepage. No caving.	
8		
9		
10		
11		
12		
13		
14		
15		
16		
17		
18		
19		
20		

**Eaglemont
Monroe, WA**

Associated Earth Sciences, Inc.

Project No. KE120280A

Logged by: TJP

Approved by: 



7/10/12

LOG OF EXPLORATION PIT NO. EP-10


Depth (ft)	<p>This log is part of the report prepared by Associated Earth Sciences, Inc. (AESI) for the named project and should be read together with that report for complete interpretation. This summary applies only to the location of this trench at the time of excavation. Subsurface conditions may change at this location with the passage of time. The data presented are a simplification of actual conditions encountered.</p> <p>DESCRIPTION</p>	
	Forest Duff / Topsoil	
1	Weathered Vashon Lodgement Till	
2	Loose, moist to very moist, reddish brown, silty SAND, with gravel, abundant roots (SM).	
3	Vashon Lodgement Till	
4	Very dense, very moist, grayish tan, silty SAND, with gravel, scattered cobbles (SM).	
5		
6	Bottom of exploration pit at depth 5.5 feet No seepage. No caving.	
7		
8		
9		
10		
11		
12		
13		
14		
15		
16		
17		
18		
19		
20		

**Eaglemont
Monroe, WA**

Associated Earth Sciences, Inc.

Project No. KE120280A

Logged by: TJP

Approved by: 



7/10/12